

Revision Date 17-Feb-2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product code DA7560
Product name Free Ride
Recommended Use Lubricant

Supplier Drummond American
A Lawson Products Company
600 Corporate Woods Parkway
Vernon Hills, IL 60061
(847) 913-9313

Emergency telephone number (888) 426-4851

2. HAZARDS IDENTIFICATION**Emergency Overview**

Harmful by inhalation. Flammable.

Color Colorless**Odor** Slight Sweet Solvent**Form** Aerosol**Aggravated Medical Conditions** None Known.**Principal Routes of Exposure** Inhalation. Eyes. Skin.**Potential health effects**

Eyes Irritation. Redness. Burning sensation.

Skin Repeated or prolonged exposure may cause:. Itching. Redness. Burning sensation.

Inhalation Headaches. Dizziness. Nausea. Loss of coordination. Irritating to respiratory system. Central nervous system effects. Extreme overexposure may cause. Possible unconsciousness. Death. Misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.

Ingestion May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Butane	106-97-8	10-30
Graphite	7782-42-5	0.5-1.5
Propane	74-98-6	10-30
Heptane (n-)	142-82-5	30-60
Toluene	108-88-3	0.5-1.5
Isopropyl Alcohol	67-63-0	15-40

4. FIRST AID MEASURES

Eye contact	Flush with plenty of water for at least 15 minutes. Seek medical attention.
Skin contact	Wash area thoroughly with soap and water. Remove and wash contaminated clothing before re-use.
Ingestion	Do not induce vomiting. Seek medical attention immediately.
Inhalation	Remove from exposure. Restore breathing. Keep warm and quiet. Contact physician if breathing difficulty develops.

5. FIRE FIGHTING MEASURES

Flash point °C	< -17.78
Flash point °F	< 0
Method	No information available

Autoignition temperature °C	No data available
Autoignition temperature °F	No data available

Flammability Limits (% in Air)

Upper	12.7
Lower	1.0

Specific Information for Aerosol Products

Flame extension	18-36 in
Flashback	Yes

Suitable extinguishing media

Carbon dioxide (CO₂). Dry chemical. Foam.

Special protective equipment for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Special Fire-Fighting Procedures

Firefighters should wear NIOSH/MSHA approved (or equivalent) self-contained pressure-demand breathing apparatus and full protective clothing. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Specific hazards

Keep product and empty container away from heat and sources of ignition

Fire and Explosion Hazards

Containers may vent or burst under extreme or prolonged fire conditions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Sensitivity to shock

No information available.

Sensitivity to static discharge

No information available.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up

Eliminate all sources of ignition. Ventilate area to maintain exposure below permissible exposure limits. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Handling

Vapors may accumulate readily and may ignite explosively. Ensure adequate ventilation. Do not smoke. Keep away from open flames, hot surfaces and sources of ignition. Do not puncture or incinerate. Do not take internally. Ground and bond containers when transferring material. Contents under pressure.

Storage

Store in temperatures below 120 degrees F. Keep away from heat and sources of ignition. Containers exposed to extreme heat may burst. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Heptane (n-)	2000 mg/m ³ 500 ppm	-	400 ppm	500 ppm
Isopropyl Alcohol	400 ppm 980 mg/m ³	-	200 ppm	400 ppm
Propane	1000 ppm 1800 mg/m ³	-	1000 ppm	-
Butane	800 ppm	-	1000 ppm	-
Toluene	200 ppm	300 ppm	20 ppm	-
Graphite	-	-	2 mg/m ³ all forms except graphite fibers	-

Ventilation and Environmental Controls

Use enough ventilation, local exhaust at the work area, general, or both, to keep below the TLV's in the worker's breathing zone and the general area. General: as necessary.

Hygiene measures

Wash hands after handling the product.

Other precautions

Avoid contact with skin and eyes

Personal protective equipment

Respiratory protection

If the exposure limits are exceeded, a NIOSH/MSHA approved respirator is recommended. Avoid breathing concentrated vapors or particles from all products not specifically designed to be inhaled.

Hand Protection

Gloves are not required in normal use. Gloves are recommended to prevent prolonged or repeated contact. Chemical resistant gloves.

Eye protection

Wear safety glasses with side shields.

Skin and body protection

None necessary under normal conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Aerosol	Color	Colorless
Odor	Slight Sweet Solvent	Odor Threshold	No information available
pH	No data available	Specific Gravity	0.66
Vapor pressure	No data available	Vapor density	>Air
Evaporation Rate	>1 (Ether =1)	VOC Content	98.8
Water solubility	No data available	Partition Coefficient (n-octanol/water)	No data available
Boiling point/range °C	< -18-114	Boiling point/range °F	< 0-238
Melting point/range °C	Not Applicable	Melting point/range °F	Not Applicable
Flash point °C	< -17.78	Flash point °F	< 0

10. STABILITY AND REACTIVITY**Stability**

Stable.

Conditions to avoid

None known.

Incompatibility

None known.

Hazardous Decomposition Products

Carbon dioxide. Carbon monoxide.

Polymerization

Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION**Component Information**

Chemical Name	LD50 (oral,rat)	LD50 (dermal,rat/rabbit)	LC50 (inhalation,rat)
<i>Heptane (n-)</i> 142-82-5	3000 mg/kg	3000	3000 mg/kg
<i>Isopropyl Alcohol</i> 67-63-0	12800 mg/kg	12800	12800 mg/kg
<i>Propane</i> 74-98-6	658 mg/L	658	658 mg/L
<i>Butane</i> 106-97-8	658 mg/L	658	658 mg/L
<i>Toluene</i> 108-88-3	12.5 mg/L	12.5	12.5 mg/L
<i>Graphite</i> 7782-42-5	-	-	-

Synergistic Products

None known

Potential health effects**Sensitization**

None known .

Mutagenic effects

None known .

Reproductive toxicity

None known .

Chronic toxicity

See Section 2 .

Teratogenic effects

None known .

Target Organ Effects

Liver. Urinary system. Cardiovascular system. Nervous system.

Carcinogenic effects

See table below

Chemical Name	ACGIH OEL - Carcinogens	IARC	NTP - Known Carcinogens	NTP - Suspected Human Carcinogens	OSHA RTK Carcinogens
Heptane (n-)	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Isopropyl Alcohol	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Propane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Butane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Toluene	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Graphite	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Heptane (n-)

Water Flea Data*Daphnia magna* hEC50 24 (>10 mg/L)

Isopropyl Alcohol

Microtox Data*Photobacterium phosphoreum* EC50=35390 mg/L (5 min)**Water Flea Data***Daphnia magna* hEC50 48 (13299 mg/L)

Toluene

Microtox Data*Photobacterium phosphoreum* EC50=19.7 mg/L (30 min)**Water Flea Data**

water flea hEC50 48 (11.3 mg/L)

water flea hEC50 48 (310 mg/L)

Daphnia magna hEC50 48 (11.3 mg/L)

water flea hEC50 48 (11.3 mg/L)

13. DISPOSAL CONSIDERATIONS**Disposal Information**

Waste must be tested for ignitability to determine EPA hazardous waste numbers. Do not incinerate. Depressurize before disposal. Dispose in accordance with federal, state, and local regulations.

Waste from residues / unused products

As supplied, this product is a RCRA Hazardous Waste .

14. TRANSPORT INFORMATION**DOT**

Consumer commodity, ORM-D

TDG

UN1950 AEROSOLS, flammable, 2.1

IMDG/IMO

UN1950 Aerosols, flammable, 2.1

IATA

UN1950 Aerosols, flammable, 2.1

MEX

UN1950 Aerosols, flammable, 2.1

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Isopropyl Alcohol	Listed
Toluene	Listed

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
Heptane (n-)	Listed	Listed	Not Listed
Isopropyl Alcohol	Not Listed	Listed	Not Listed
Propane	Listed	Listed	Not Listed
Butane	Listed	Listed	Not Listed
Toluene	Listed	Listed	Developmental
Graphite	Not Listed	Listed	Not Listed

Chemical Name	EINECS	DSL	NDSL	TSCA
Heptane (n-)	X	X	-	X
Isopropyl Alcohol	X	X	-	X
Propane	X	X	-	X
Butane	X	X	-	X
Toluene	X	X	-	X
Graphite	X	X	-	X

CPRC

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations

16. OTHER INFORMATION

NFPA		HMIS	
Health	2	Health	-
Flammability	4	Flammability	-
Reactivity	0	Physical Hazard	-

Prepared By

Michael Katz, Regulatory Affairs Specialist

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.